


PRO-VAC 164-70

SELF RELEASING VACUUM BAGGING FILM

Description:

- A self-releasing multilayer PA/PO vacuum film designed for processing of hollow composite structures.
- Is idea of both oven and autoclave applications.
- Compatible with epoxy and phenolic pre pregs.
- Small widths are supplied as a gusseted tube to simplify placement in a closed mould process.



Technical data:

Part number	PRO-VAC 164-70	
Colour	Green or Red	
Width	0,086 m to 2,3 m wide	
Thickness	70 μ +/-10%	ISO 4593
Elongation (break)	MD 445% +/- 15%	ASTM D882
	TD 350% +/-15%	ASTM D882
Tensile (break)	MD 50 N/mm ² +/-15%	ASTM D882
	TD 42 N/mm ² +/-15%	ASTM D882
Maximum use temp	160°C	

Packaging and storage

Standard packaging is a strong bubble plastic; the rolls can be packaged in cardboard tubes if requested by customer.

This film contains a significant percentage of nylon which is hydrophobic therefore the film's characteristics may change dependent on workshop and storage environment. The lower the humidity, the stiffer the film will feel.

Store in original packaging.



HF Industri & Marine ApS

HF Industri & Marine ApS Gotlandsvej 6 5700 Svendborg Denmark
Phone: +45 62 20 13 12 • Fax: +45 62 20 14 77 • info@hfmarine.dk • www.hfmarine.dk