

PRO-VAC MLR-5 and MLR-3

REINFORCED TEFLON MOULD RELEASE

Description:

- High quality self-adhesive Teflon coated glass mould release for composite processing applications.
- Adheres to composite and metal tools as well as wooden moulds and plugs.
- The adhesive system is pressure sensitive therefore is stable throughout vacuum and autoclave curing.
- Recommended for use on flat or single curvature surfaces, can be joined using a butt joint.

Technical data:

Part number	PRO-VAC MLR-5	PRO-VAC MLR-3
Reinforcement	woven glass	Woven glass
Coating	PTFE	PTFE
PTFE content	55%	67%
Adhesive	Silicone	Silicone
Nominal coated fabric thickness	0,116 mm	0.07 mm
Adhesive weight	55 g/m ²	50 g/m ²
Peel Adhesion	12 N/ 2.5cm	12 N/ 2.5cm
Max use temperature	260°C	260°C
Width	1000 mm	1000 mm



Packaging and storage

Store in original packing at room temperature (22 °C).
Shelf life of 8 months from date of manufacture.



HF Industri & Marine ApS

HF Industri & Marine ApS Gotlandsvej 6 5700 Svendborg Denmark
Phone: +45 62 20 13 12 • Fax: +45 62 20 14 77 • info@hfmarine.dk • www.hfmarine.dk